

Linux Networking Basics

Franz Schäfer

Linux LV, WU Wien

April 27, 2018

②Copyleft: This Document may be distributed under GNU GFDL or under Creative Commons
CC BY-SA 3.0

Table of contents

- ① preface
- ② Networking Basics
- ③ commands to access interfaces
- ④ Linux Firewalling, VLANs

About this slides

<http://mond.at/cd/>

This slides are Copyleft: CC-BY-SA, Use them as you like.

This is the first in a series of 3 lectures on Linux:

- ① Networking
- ② Server, SSH
- ③ Backup, Boot, LVM, Virtualization


About Me

- Storage Architect @ sIT-Solutions
- Sysadmin @ IST Austria, head of IT
- Sysadmin @ ZID WU
- ISP (akis, silverserver, ...)
- Nachrichtentechnik, Regelungstechnik, Computertechnik
- Linux User since 1995 (kernel 1.1.18)

Network Abstraction in Linux


- Physical Connection
 - Ethernet, UTP, Wireless
 - Serial Cable
 - Virtual Connection (Tunnel, VPN)
- Linux Kernel: Interface
- Network Stack: e.g. TCP/IP (in Kernel)
- Userspace Programs: E.g. Webbrowser

Network Abstraction in Linux



linux networking. CC-BY-SA 3.0
Image of Network Card: <https://de.wikipedia.org/wiki/Netzwerkkarte>

ISO OSI 7 Layer



ifconfig

```
# /sbin/ifconfig
```


```
eth0      Link encap:Ethernet HWaddr 80:ee:73:83:a9:1e
          inet addr:192.168.79.79  Bcast:192.168.79.255  Mask:255.255.255.0
          inet6 addr: fe80::82ee:73ff:fe83:a91e/64 Scope:Link
            UP BROADCAST RUNNING MULTICAST  MTU:1500  Metric:1
            RX packets:260357 errors:0 dropped:0 overruns:0 frame:0
            TX packets:225288 errors:0 dropped:0 overruns:0 carrier:0
            collisions:0 txqueuelen:1000
            RX bytes:261709698 (249.5 MiB)  TX bytes:29802129 (28.4 MiB)
```

ip tool

```
# ip addr
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast state UP group default qlen 1000
    link/ether 80:ee:73:83:a9:1e brd ff:ff:ff:ff:ff:ff
    inet 192.168.79.79/24 brd 192.168.79.255 scope global eth0
        valid_lft forever preferred_lft forever
    inet6 fe80::82ee:73ff:fe83:a91e/64 scope link
        valid_lft forever preferred_lft forever

# ip -s link
2: eth0: <BROADCAST,MULTICAST,UP,LOWER_UP> mtu 1500 qdisc pfifo_fast state UP mode DEFAULT group default qlen 1000
    link/ether 80:ee:73:83:a9:1e brd ff:ff:ff:ff:ff:ff
    RX: bytes   packets   errors   dropped overrun mcast
    261967909   261306      0        0        0        0
    TX: bytes   packets   errors   dropped carrier collsns
    29989420   296506      0        0        0        0
```

Ethernet



- All nodes can "see" each other
- addressing via MAC address: e.g.: A3:07:56:3C:F3:02
- broadcast to all is possible

IPv4

2^{32} addresses written in the 256^4 notation:

e.g.: 113.251.19.71

not a valid address: 64.311.17.92

On ethernet: relation of MAC addresses and IP addresses via *arp* protocol

```
# arp -n
```

IPv6

```
# host -t AAAA www.google.com
www.google.com has IPv6 address 2a00:1450:400c:c0b::68
```

2^{128} addresses written as 8 blocks of 4 hex digits.

consecutive blocks of 0 can be written as :: (only once per address)

e.g.: ::1

Tools: ping6, traceroute6, “ip -6”

CIDR

Classless Internet Domain Routing

$123.24.67.0/24 = 123.24.67.XXX$

$137.208.0.0/16 = \text{WU-Network} = 137.208.\text{xxx}.xxx$

$123.24.67.128/25 = 123.24.67.128 \text{ to } 123.24.67.255$

Alternativ: netmask: 255.255.255.128

Private IP Space: RFC 1918

- 10.0.0.0 to 10.255.255.255
10.0.0.0/8 or e.g. divided into 65536 times /24
- 172.16.0.0 to 172.31.255.255
172.16.0.0/12 e.g. divided into 1024 /24 networks
- 192.168.0.0 to 192.168.255.255
192.168.0.0/16 gives 256 networks with /24

e.g.: your home IP and network:

192.168.1.13/24

not routed in the public internet: you need NAT

network manager

GUI interface uses NetworkManager to manage networks.
should be disabled on a server
can be controlled via comandline via nmcli

alias interface

```
# ifconfig eth0:2 192.168.201.42 \
netmask 255.255.255.0 \
broadcast 192.168.201.255
# ifconfig eth0:2 192.168.201.42/24
```

additional IP address on an existing interface:

```
# ip addr add 192.168.202.123/24 dev eth0
```

tcpdump - look at your traffic

```
# tcpdump -ni eth0 not port 22

13:40:09.295326 IP 213.235.242.217.4569 >
    193.238.157.20.4569: UDP, length 12
13:40:09.322544 IP 141.89.64.1.27650 >
    193.238.157.20.53: 16832% [1au] AAAA? dns.mond.at. (40)
13:40:09.322785 IP 193.238.157.20.53 >
    141.89.64.1.27650: 16832* 0/1/1 (88)
13:40:09.483043 arp who-has 192.168.30.32
    (ff:ff:ff:ff:ff:ff) tell 192.168.30.32
13:40:09.516130 IP 194.168.8.110.32771 >
    193.238.157.20.53: 57265 MX? area23.mond.at. (32)
```

ping



```
# ping www.google.com
PING www.l.google.com (209.85.135.147) 56(84) bytes
of data.
64 bytes from mu-in-f147.google.com (209.85.135.147):
icmp_seq=1 ttl=241 time=22.6 ms
64 bytes from mu-in-f147.google.com (209.85.135.147):
icmp_seq=2 ttl=241 time=22.6 ms
```


traceroute

```
# traceroute www.google.com

traceroute to www.l.google.com (209.85.135.103),
30 hops max, 40 byte packets

1 gw-2-254.wu-wien.ac.at (137.208.254.254)
    0.793 ms  0.769 ms  0.752 ms
2 box-1-19.wu-wien.ac.at (137.208.19.135)
    0.849 ms  0.810 ms  0.879 ms
...
14 mu-in-f103.google.com (209.85.135.103)
    23.536 ms  23.664 ms  23.336 ms
```

route - how the packets find their way



route - a few examples

```
# route -n
# route add default gw 192.168.1.1
# route add -net 192.168.2.0/24 gateway 192.168.1.7
```

turn on ip forwarding

per default packets are not forwarded from one interface to another

in /etc/sysctl.conf

```
net.ipv4.ip_forward=1  
net.ipv4.conf.all.rp_filter=0
```

or

```
# echo 1 > /proc/sys/net/ipv4/ip_forward  
# echo 0 > /proc/sys/net/ipv4/conf/all/rp_filter
```

dhcp client

```
# dhclient -v eth0
```

```
Internet Systems Consortium DHCP Client 4.3.1
Copyright 2004-2014 Internet Systems Consortium.
All rights reserved.
For info, please visit https://www.isc.org/software/dhcp/
```

```
Listening on LPF/eth0/80:ee:73:83:a9:1e
Sending on LPF/eth0/80:ee:73:83:a9:1e
Sending on Socket/fallback
DHCPREQUEST on eth0 to 255.255.255.255 port 67
DHCPNAK from 192.168.79.1
DHCPDISCOVER on eth0 to 255.255.255.255 port 67 interval 8
DHCPREQUEST on eth0 to 255.255.255.255 port 67
DHCPOffer from 192.168.79.1
DHCPACK from 192.168.79.1
bound to 192.168.79.108 -- renewal in 34746 seconds.
```

ifup / ifdown

```
# ifup eth1
# ifup -a

config file: /etc/network/interfaces

auto lo
iface lo inet loopback

auto eth1
iface eth1 inet dhcp
```

/etc/network/interfaces

```
auto eth0
iface eth0 inet static
address 192.168.17.42
network 192.168.17.0
netmask 255.255.255.0
broadcast 192.168.17.255
gateway 192.168.17.1
up /root/myfirewall.sh
```

troubleshooting part 1

- ifconfig eth0 works?
check modprobe
for wireless: iwconfig, wpa_supplicant
- do we have the right IP address in ifconfig or ip addr
e.g. use dhclient
- check route -n

troubleshooting part 2

- ifconfig shows incoming packets?
- tcpdump -ni shows packets?
- ping a machine in the local network (e.g. gateway)
 - check arp -n
 - do we see the mac address of the gateway?
- try a traceroute to an outside address
- maybe it is a dns problem
 - ip address works but names do not.

TCP and UDP port numbers

TCP — network stack takes care about providing the illusion of a connection

UDP — you only send packets. they may get lost or may arrive in the wrong order.

Well known ports


tcp 80 www

tcp 25 smtp (email sending)

tcp 22 ssh

udp 53 dns

iptables



iptables filter examples

show rules:

```
# iptables -L -n  
# iptables -L -n -t nat
```

flush rules:

```
# iptables -F
```

protect access to SSH:

```
# iptables -I INPUT -j DROP -i eth1 -p tcp \  
--dport 22 -s 0/0  
# iptables -I INPUT -j ACCEPT -s 182.16.21.0/24 \  
-p tcp --dport 22
```

iptables nat

```
# iptables -t nat -I POSTROUTING -j SNAT \
-s 10.0.0.0/8 -d ! 10.0.0.0/8 \
--to-source 123.231.12.222
```


```
# iptables -t nat -I POSTROUTING \
-j MASQUERADE -s 192.168.1.0/24 \
--out-interface eth1
```

why VLANs?

We want multiple networks on the same physical cable to connect networks over different switches:

IEEE 802.1q adds a 12bit VLAN tag to each ethernet packet so we can have about 4096 different VLANs.

VLANs example diagram



Linux VLAN commands

```
# ifconfig eth0 up
# vconfig add eth0 101
# vconfig add eth0 201

# ifconfig eth0.101 192.168.123.45 ....
```

can also be done in /etc/network/interfaces

installing openvpn

```
# apt-get install openvpn
# cd /usr/share/doc/openvpn/examples/sample-config-files
# zcat examples/sample-config-files/server.conf.gz \
> /etc/openvpn/mondbasis.conf
# openssl dhparam -out dh2048.pem 2048
# chdir /etc/openvpn/
# mkdir cd

copy easy-rsa scripts
and edit ./vars
# ./build-ca
# ./build-key-server openvpn.mond.at
# ./build-key-pass mondhandy@mond.at
```

installing openvpn

```
edit /etc/default/openvpn
```

```
to select the configuration to start on boot
```

```
# /etc/init.d/openvpn restart
```

```
check logs
```

```
# journalctl -xn
```

```
# tail -100 /var/log/syslog
```

```
openvpn should be listening on port 1194 udp
```

```
# netstat -nu --listen -p
```

openvpn point to point link

```
# ifconfig
```

```
tun0      Link encap:UNSPEC HWaddr 00-00-00-00-00-00-00-00-00-00-00-00-00-00-00-00-00-00-00-00  
          inet addr:10.17.17.1 P-t-P:10.17.17.2 Mask:255.255.255.255  
          UP POINTOPOINT RUNNING NOARP MULTICAST MTU:1500 Metric:1  
          RX packets:0 errors:0 dropped:0 overruns:0 frame:0  
          TX packets:0 errors:0 dropped:0 overruns:0 carrier:0  
          collisions:0 txqueuelen:100  
          RX bytes:0 (0.0 B) TX bytes:0 (0.0 B)
```